



Sony Ericsson Xperia Pro MK16A Logic Board Replacement

In this guide we will be getting inside the phone and showing how to detach the logic board.

Written By: Craig



INTRODUCTION

This guide will help you replace the logic board on your Sony Ericsson Xperia Pro MK16A phone. Follow along and you will have a new logic board installed in about half an hour.



TOOLS:

- [T6 Torx Screwdriver](#) (1)
 - [Phillips #0 Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
-

Step 1 — Taking the Back Off



- Use a plastic opening tool to get the back cover off your phone.

✦ The plastic opener will work on any side, but be careful and pry gently.

Step 2 — Removing the Battery




- Locate the battery in your phone.
- Find the divot below the battery.
- Use your thumb to lift the battery out of the phone.

Step 3 — Remove Screws




- Remove the 4 black screws with the Phillips screwdriver.
- Remove the 4 silver screws with the Torx screwdriver.

Step 4 — Remove Back Case





- Insert the plastic opening tool in between the two halves of the case. Pry around the phone to detach the back case.

Step 5 — Access the Logic Board



- Remove the last screw that is connecting the logic board using the Phillips screwdriver.
- Undo the two ribbons.

Step 6 — Remove the Logic Board



- Undo that last connector.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-18 10:52:18 PM.